

LEDLINE AIR 1617 WHT - COMBO SYSTEM

3D Bending · Static White

(Standard Cut + Free Cut Finishing Piece)


Features

The AIR 1617 Combo System combines standard cut and free cut capabilities to provide precise, made-to-order lengths, utilizing Standard Cuts for the majority of the runs, with Free Cuts reserved only for the finishing segments. This combo usage achieves cost savings of 20–40% versus using Free Cuts for the entire length. Both AIR 1617 Standard Cut and Free Cut maintain consistent binning and brightness.

Applications

Living rooms, TV walls, feature walls, under-cabinet areas, staircases, ceiling coves, hallways, etc.


Date	Fixture type
Project name	Project phase



Combo System



Bending Directions & Diameters



Order Code

Assembly Builder

Model	Bend Direction	Voltage	CCT	Power	Left Feed Entry
AIR1617	3D-3D bending	24V-DC24V	927-RA90 2700K	100-10W/M	F Front
	3DFC-3D bending Free Cut		930-RA90 3000K		B Bottom
			940-RA90 4000K		S Side
				C Closed	

*AIR16173DFC: Free Cut delivers precise field-cut lengths for the last segment, while keeping in line with standard cut in dimensions, binning, output, and mounting for a uniform appearance.

Assembly Builder

Mounting Order Code

Right Feed Entry	Length
F Front	Max. nominal 5m(16.4ft) AIR16173D
B Bottom	Max. nominal 4m(13.12ft) AIR16173DFC
S Side	Increment 62.5mm(2.46in.)
C Closed	

Product Code
Please select on the Mounting Options page

*We will list the nearest actual manufacturing length on the quotation, based on your requested length.

LEDLINE AIR 1617 WHT - COMBO SYSTEM

3D Bending · Static White

(Standard Cut + Free Cut Finishing Piece)

Lumen Output (lm/m)

CCT	10W/M
■ 2700K	970
■ 3000K	1010
■ 4000K	1040
Max. Run for standard cut	5m
Max. run for Free cut	4m


Technical Details

Efficacy	101lm/W @3000K 10W
CRI	Ra>90
Beam Angle	110°
LED MacAdam	3 step
IK Rating	IK08
Average Life (L80B50)	>44,000 hours
Storage Temperature	-40°C- 65°C
Operating Temperature	-40°C- 65°C

Photometry

AIR16173D-24-930-100

LEDLINE AIR 1617, 3D bending, 24V, RA90, 3000K, 10W/M



Zonal Lumen Summary

Zone	Lumen	% Fixture
0-30	254.0	25.3%
0-40	415.6	41.4%
0-60	737.2	73.4%
0-90	971.1	96.7%
0-180	1004.0	100.0%


LEDLINE AIR 1617 WHT - COMBO SYSTEM

(Standard Cut + Free Cut Finishing Piece)


3D Bending · Static White

Feed Entry / End Cap Options

FT: Flush Translucent – IP67, factory-made only




Silicone end cap – IP67, for field cuttable only



Connector Wire Options



OW: Open wire, **Dry** only
Standard 30cm (0.98ft), 20 AWG,
wire length customizable



MC: Male connector, **Wet**
Standard 30cm (0.98ft), 20 AWG



















FC: Female connector, **Wet**
Standard 30cm (0.98ft), 20 AWG

LEDLINE AIR 1617 WHT - COMBO SYSTEM

(Standard Cut + Free Cut Finishing Piece)

3D Bending · Static White


Mounting Options

			<p>AC167-AP</p> <table border="1"> <tr> <td>Name</td> <td>Straight surface profile</td> </tr> <tr> <td>Material</td> <td>Aluminum</td> </tr> <tr> <td>Standard Length</td> <td>1M (3.28ft)</td> </tr> </table>	Name	Straight surface profile	Material	Aluminum	Standard Length	1M (3.28ft)		
Name	Straight surface profile										
Material	Aluminum										
Standard Length	1M (3.28ft)										
			<p>AC167-CR</p> <table border="1"> <tr> <td>Name</td> <td>Bendable surface profile</td> </tr> <tr> <td>Material</td> <td>Aluminum</td> </tr> <tr> <td>Standard Length</td> <td>1M (3.28ft)</td> </tr> <tr> <td>Min. Bending Diameter</td> <td>600mm(23.6in.)</td> </tr> </table>	Name	Bendable surface profile	Material	Aluminum	Standard Length	1M (3.28ft)	Min. Bending Diameter	600mm(23.6in.)
Name	Bendable surface profile										
Material	Aluminum										
Standard Length	1M (3.28ft)										
Min. Bending Diameter	600mm(23.6in.)										
			<p>AC167-EP</p> <table border="1"> <tr> <td>Name</td> <td>Straight recessed profile</td> </tr> <tr> <td>Material</td> <td>Aluminum</td> </tr> <tr> <td>Standard Length</td> <td>1M (3.28ft)</td> </tr> </table>	Name	Straight recessed profile	Material	Aluminum	Standard Length	1M (3.28ft)		
Name	Straight recessed profile										
Material	Aluminum										
Standard Length	1M (3.28ft)										
			<p>AC167-LP</p> <table border="1"> <tr> <td>Name</td> <td>Mud-in profile</td> </tr> <tr> <td>Material</td> <td>Aluminum</td> </tr> <tr> <td>Standard Length</td> <td>1M (3.28ft)</td> </tr> </table>	Name	Mud-in profile	Material	Aluminum	Standard Length	1M (3.28ft)		
Name	Mud-in profile										
Material	Aluminum										
Standard Length	1M (3.28ft)										
			<p>AC167-SCRL</p> <table border="1"> <tr> <td>Name</td> <td>Bendable mud-in profile</td> </tr> <tr> <td>Material</td> <td>Aluminum</td> </tr> <tr> <td>Standard Length</td> <td>1M (3.28ft)</td> </tr> <tr> <td>Min. Bending Diameter</td> <td>600mm(23.6in.)</td> </tr> </table>	Name	Bendable mud-in profile	Material	Aluminum	Standard Length	1M (3.28ft)	Min. Bending Diameter	600mm(23.6in.)
Name	Bendable mud-in profile										
Material	Aluminum										
Standard Length	1M (3.28ft)										
Min. Bending Diameter	600mm(23.6in.)										
			<p>AC167-SGP</p> <table border="1"> <tr> <td>Name</td> <td>Straight surface profile</td> </tr> <tr> <td>Material</td> <td>Aluminum with silicone groove</td> </tr> <tr> <td>Standard Length</td> <td>1M (3.28ft)</td> </tr> </table>	Name	Straight surface profile	Material	Aluminum with silicone groove	Standard Length	1M (3.28ft)		
Name	Straight surface profile										
Material	Aluminum with silicone groove										
Standard Length	1M (3.28ft)										
			<p>AC167-CSGP</p> <table border="1"> <tr> <td>Name</td> <td>Bendable surface profile</td> </tr> <tr> <td>Material</td> <td>Aluminum with silicone groove</td> </tr> <tr> <td>Standard Length</td> <td>1M (3.28ft)</td> </tr> <tr> <td>Min. Bending Diameter</td> <td>600mm(23.6in.) only side bend</td> </tr> </table>	Name	Bendable surface profile	Material	Aluminum with silicone groove	Standard Length	1M (3.28ft)	Min. Bending Diameter	600mm(23.6in.) only side bend
Name	Bendable surface profile										
Material	Aluminum with silicone groove										
Standard Length	1M (3.28ft)										
Min. Bending Diameter	600mm(23.6in.) only side bend										
			<p>AC167-BA</p> <table border="1"> <tr> <td>Name</td> <td>Light-block profile</td> </tr> <tr> <td>Material</td> <td>Aluminum</td> </tr> <tr> <td>Standard Length</td> <td>1M (3.28ft)</td> </tr> </table>	Name	Light-block profile	Material	Aluminum	Standard Length	1M (3.28ft)		
Name	Light-block profile										
Material	Aluminum										
Standard Length	1M (3.28ft)										


LEDLINE AIR 1617 WHT - COMBO SYSTEM

(Standard Cut + Free Cut Finishing Piece)

3D Bending · Static White




AC167-PC	
Name	PC profile
Material	Polycarbonate
Standard Length	1M (3.28ft)




AC167-CPC	
Name	Bendable PC profile
Material	Polycarbonate
Standard Length	1M (3.28ft)
Min. Bending Diameter	300mm (11.8in.)

Clip Options




AC167-MC	
Name	Mounting clip
Material	Aluminum
Standard Length	25mm (0.98in.)


Bracket Options



AC167-SET-LA	
Name	L-shaped mounting bracket
Material	Aluminum
Standard Length	20mm (0.79in.)
* AC167-SET-LA must be installed with AC167-AP	



AC167-AMB	
Name	Adjustable mounting clip
Material	Stainless steel
Standard Length	25.5mm (1 in.)
* AC167-AMB must be installed with AC167-AP	



AC167-SET-LC	
Name	Spring clip
Standard Pkg	1pcs
* AC167-SET-LC must be installed with AC167-EP	

Tool Options



IF-167	
Name	Fixture
Material	Resin
Standard Pkg	1pcs
* Insertion Fixture for AC167-CPC	

LEDLINE AIR 1617 WHT - COMBO SYSTEM

(Standard Cut + Free Cut Finishing Piece)

3D Bending · Static White

Silicone End Caps (Optional, purchase for extra)

AC167-EC
Silicone closed end cap



AC167-EC2-F
Silicone end cap front entry with
30cm(0.98ft) cable, 2 pin



AC167-EC2-S
Silicone end cap side entry with
30cm(0.98ft) cable, 2 pin



AC167-EC2-B
Silicone end cap bottom entry with
30cm(0.98ft) cable, 2 pin

Additional Accessories (Optional, purchase for extra)

AD102-2-MCW
Male connector,
30cm (0.98ft) white cable,
2 pin, IP67, Wet, 20 AWG



AD102-2-FCW
Female connector,
30cm (0.98ft) white cable,
2 pin, IP67, Wet, 20 AWG



AD102-2-MCW
Male connector,
30cm (0.98ft) black cable,
2 pin, IP67, Wet, 20 AWG



AD102-2-FCW
Female connector,
30cm (0.98ft) black cable,
2 pin, IP67, Wet, 20 AWG



AF001-1
1 Adjustable angle scissors set,
with 4 spare blades

LEDLINE AIR 1617 WHT - COMBO SYSTEM

3D Bending · Static White

(Standard Cut + Free Cut Finishing Piece)

Drivers

Non-dimmable

Code	Max Load	Input	Output	Environment	Size (L x W x H)
ELG-150-24A-3Y	150W	100-305VAC	24V	Dry/Damp/IP67	219 * 63 * 35.5 mm
LRS-150-24	150W	85-132VAC / 170-264VAC	24V	Dry	159 * 97 * 30 mm

3 in 1-dimmable


Code	Max Load	Input	Output	Environment	Size (L x W x H)
ELG-150-24B-3Y	150W	100-305VAC	24V	Dry/Damp/IP67	219 * 63 * 35.5 mm

DALI-dimmable


Code	Max Load	Input	Output	Environment	Size (L x W x H)
ELG-150-24DA-3Y	150W	100-305VAC	24V	Dry/Damp/IP67	219 * 63 * 35.5 mm

Wiring Diagram


Non-dimmable



3 in 1-dimmable



DALI-dimmable



LEDLINE AIR 1617 WHT - COMBO SYSTEM

3D Bending · Static White

(Standard Cut + Free Cut Finishing Piece)

24V Voltage Drop & Maximum Wire Length Chart

Based on 24V voltage with a 3% voltage drop allowance. Indicates the maximum wire length from the power supply to the start of the run.

Total load	8AWG	10AWG	12AWG	14AWG	16AWG	18AWG	20AWG	22AWG
10W / 0.4A	484.0m	304.5m	191.4m	120.4m	75.5m	47.5m	29.8m	18.5m
20W / 0.8A	242.0m	152.1m	95.7m	60.0m	37.8m	23.7m	14.9m	9.1m
30W / 1.3A	161.2m	101.5m	63.7m	39.9m	24.9m	15.8m	9.7m	6.1m
40W / 1.7A	121.0m	75.9m	47.8m	29.8m	18.9m	11.8m	7.3m	4.5m
50W / 2.1A	96.6m	60.6m	38.1m	24.0m	14.9m	9.4m	5.7m	3.6m
60W / 2.5A	80.4m	50.6m	31.7m	19.8m	12.5m	7.9m	4.8m	3.0m
70W / 2.9A	68.8m	43.2m	27.1m	17.0m	10.6m	6.7m	4.2m	2.4m
80W / 3.3A	60.3m	37.8m	23.7m	14.9m	9.4m	5.7m	3.6m	2.1m
90W / 3.8A	53.6m	33.8m	21.0m	13.1m	8.2m	5.1m	3.0m	1.8m
100W / 4.2A	48.1m	30.1m	18.9m	11.8m	7.3m	4.5m	2.7m	1.8m
110W / 4.6A	43.8m	27.4m	17.3m	10.6m	6.7m	4.2m	2.7m	1.5m
120W / 5.0A	40.2m	25.3m	15.8m	9.7m	6.1m	3.9m	2.4m	1.5m
130W / 5.4A	37.1m	23.1m	14.6m	9.1m	5.7m	3.6m	2.1m	1.2m
140W / 5.8A	34.4m	21.6m	13.4m	8.5m	5.1m	3.3m	2.1m	1.2m
150W / 6.3A	32.0m	20.1m	12.5m	7.9m	4.8m	3.0m	1.8m	1.2m
160W / 6.7A	30.1m	18.9m	11.8m	7.3m	4.5m	2.7m	1.8m	0.9m
170W / 7.1A	28.3m	17.6m	10.9m	7.0m	4.2m	2.7m	1.5m	0.9m
180W / 7.5A	26.8m	16.7m	10.3m	6.7m	3.9m	2.4m	1.5m	0.9m
190W / 7.9A	25.3m	15.8m	10.0m	6.0m	3.9m	2.4m	1.5m	0.9m
200W / 8.3A	24.0m	14.9m	9.4m	5.7m	3.6m	2.1m	1.2m	0.9m
210W / 8.8A	22.8m	14.3m	8.8m	5.4m	3.3m	2.1m	1.2m	0.6m
220W / 9.2A	21.9m	13.7m	8.5m	5.4m	3.3m	2.1m	1.2m	0.6m
230W / 9.6A	21.0m	13.1m	8.2m	5.1m	3.0m	1.8m	1.2m	0.6m
240W / 10.0A	20.1m	12.5m	7.9m	4.8m	3.0m	1.8m	1.2m	0.6m
250W / 10.4A	19.2m	12.1m	7.6m	4.5m	2.7m	1.8m	0.9m	0.6m